

## Manhole Clamp

---

### Product information



The manhole clamp is used for the transport and laying of manholes. No adjustment of the clamping range is necessary. Accidents caused by incorrect adjustment are excluded. Due to the holdfast application the clamp must not be lifted when applying and disconnecting.

#### Features:

- Simple applying and disconnecting by means of holdfast application: clamp must not be lifted manually
- No adjustment of the clamping range
- Huge multiplication guarantees optimum safety
- Manhole clamp SZA for manholes and cones according to DIN 4034 Part 1 and 2
- With spring tension
- With web sling or high-strength chains

... [Read more](#)

---

**Safety factor:** 5:1

## Manhole Clamp

### Technical data

Part code	Code	WLL ton	Jaw width mm	Weight kg
502100101203010	SZM 1	1	40-120	16
502100151203010	SZM 1.5	1.5	40-120	28
502100151203014	SZML 1.5	1.5	40-120	29
502100151203015	SZM 1.5 K	1.5	40-120	32
502100201803010	SZA 2	2	60-180	28
502100201803014	SZA 2K	2	60-180	31
502100301803010	SZA 3	3	60-180	40
502100301803014	SZAL 3	3	60-180	41
502100301803015	SZA 3 K	3	60-180	45
502100301803016	SZAL 3 K	3	60-180	47
502100401803010	SZA 4	4	60-180	55