

Horizontal Lifting Clamp TNMH

Product information



For horizontal lifting and transporting of all non-deflecting plates and structures without marking, scratching and or damaging the material surface.

Perfect for lifting materials such as (stainless) steel, aluminum, nature stone, composite, painted materials, wood, glass, plastic, etc .

Jaw openings available from: 0 to 50 mm

Features:

- Jaw and cam are covered with a special high quality pressure resistant fabric
- Compact design and high lifting capacity
- Lightweight design for easy handling
- Tough quality heavy duty welded body

... [Read more](#)

Marking: According to standard, CE-marked, Type, serial number, WLL, Jaw opening.


Temperature range: - 40°C to +50°C.

Standard: EN 13155

Note: Must always be used in pairs (or multiple pairs)

Horizontal Lifting Clamp TNMH

Blueprint



Technical data

| Part code | Code | WLL ton | Jaw width mm | H mm | S mm | T mm | U mm | V mm | W mm | X mm | Y mm | Weight kg |
|-----------------|--------|---------|--------------|------|------|------|------|------|------|------|------|-----------|
| 502100100251610 | 1 TNMH | 1 | 0-25 | 10 | 94 | 20 | 155 | 140 | 15 | 65 | 15 | 2.4 |
| 502100200451610 | 2 TNMH | 2 | 0-45 | 15 | 151 | 30.5 | 267 | 225 | 23 | 90 | 15 | 7.5 |
| 502100300451610 | 3 TNMH | 3 | 0-45 | 15 | 151 | 30.5 | 271 | 225 | 20 | 90 | 15 | 8.3 |
| 502100400501610 | 4 TNMH | 4 | 0-50 | 17.5 | 161 | 30.5 | 300 | 250 | 20 | 115 | 30 | 13 |
| 502100600501610 | 6 TNMH | 6 | 0-50 | 17.5 | 161 | 30.5 | 306 | 250 | 25 | 130 | 30 | 18 |