Lifting Solutions Group
Axel Johnson International

# Wire Rope Lifting Sling WLS-000

## Product information



**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm2***
(*ø 3mm - ø 7mm rope constrcution: 6x19M WSC 1960 N/mm2)
**Design:** Endless, mechanically pressed with 2 alu. ferrules

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope constructions possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

... *Read more*

**Note:** We recommend that the sling not is bent over a diameter less than 6 times the wire rope diameter without reducing the WLL.

**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Wire Rope Lifting Sling WLS-000

## Technical data

| Part code | Diameter mm | WLL ton |
|---|---|---|
| 1601 | 3 | 0.23 |
| 1601 | 4 | 0.42 |
| 1601 | 5 | 0.65 |
| 1601 | 6 | 0.94 |
| 1601 | 7 | 1.28 |
| 1601 | 8 | 1.64 |
| 1601 | 9 | 2.07 |
| 1601 | 10 | 2.56 |
| 1601 | 11 | 3.1 |
| 1601 | 12 | 3.67 |
| 1601 | 13 | 4.33 |
| 1601 | 14 | 5.03 |
| 1601 | 16 | 6.57 |
| 1601 | 18 | 8.3 |
| 1601 | 20 | 10.24 |
| 1601 | 22 | 12.41 |
| 1601 | 28 | 16.8 |
| 1601 | 26 | 17.33 |
| 1601 | 24 | 17.46 |
| 1601 | 32 | 20.08 |
| 1601 | 36 | 26.25 |
| 1601 | 40 | 33.19 |
| 1601 | 44 | 41.11 |
| 1601 | 48 | 49.56 |
| 1601 | 52 | 59.1 |
| 1601 | 56 | 69.38 |
| 1601 | 60 | 78 |

**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved