Lifting Solutions Group
Axel Johnson International

Wire Rope Lifting Sling WLS-176

Product information



Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm2*
(*ø 3mm - ø 7mm rope constrcution: 6x19M WSC 1960 N/mm2)
Design: Master link in one end and self-locking safety hook in other end, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request..

... *Read more*

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Wire Rope Lifting Sling WLS-176

Technical data

Part code	Diameter mm	WLL ton
1603	3	0.12
1603	4	0.21
1603	5	0.32
1603	6	0.47
1603	7	0.64
1603	8	0.82
1603	9	1.04
1603	10	1.28
1603	11	1.55
1603	12	1.84
1603	13	2.17
1603	14	2.51
1603	16	3.3
1603	18	4.1
1603	20	5.1
1603	22	6.2
1603	24	7.38
1603	26	8.66
1603	28	10.04
1603	32	13.12
1603	36	16.59

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved