

## Wire Rope Lifting Sling WLS-180

---

### Product information



**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>\***

(\*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm<sup>2</sup>)

**Design:** Master link in both ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> [Show table](#)

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request..

... [Read more](#)

---

## Wire Rope Lifting Sling WLS-180

### Technical data

Part code	Diameter mm	WLL ton
1603	3	0.12
1603	4	0.21
1603	5	0.32
1603	6	0.47
1603	7	0.64
1603	8	0.82
1603	9	1.04
1603	10	1.28
1603	11	1.55
1603	12	1.84
1603	13	2.17
1603	14	2.51
1603	16	3.3
1603	18	4.1
1603	20	5.1
1603	22	6.2
1603	24	7.38
1603	26	8.66
1603	28	10.04
1603	32	13.12
1603	36	16.59
1603	40	20.56
1603	44	24.78
1603	48	29.55