Lifting Solutions Group
Axel Johnson International

Wire Rope Lifting Sling WLS-275

Product information



Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm2
Design: Master link in one end and eyehooks with safety latch in other ends, aluminum ferrule secured (mechanical spliced).

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as top rings, shackles, hooks, etc.. possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

... *Read more*

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Wire Rope Lifting Sling WLS-275

Technical data

Part code	Diameter mm	WLL ton	WLL 0-45° t	WLL 45-60° t
1605	3	0.16	0.16	0.12
1605	4	0.29	0.29	0.21
1605	5	0.45	0.45	0.32
1605	6	0.66	0.66	0.47
1605	7	0.89	0.89	0.64
1605	8	1.15	1.15	0.82
1605	9	1.45	1.45	1.04
1605	10	1.79	1.79	1.28
1605	11	2.17	2.17	1.55
1605	12	2.57	2.57	1.84
1605	13	3.03	3.03	2.17
1605	14	3.52	3.52	2.51
1605	16	4.6	4.6	3.3
1605	18	5.81	5.81	4.1
1605	20	7.17	7.17	5.1
1605	22	8.69	8.69	6.2
1605	24	10.33	10.33	7.38
1605	26	12.13	12.13	8.66
1605	28	14.06	14.06	10.04
1605	32	18.37	18.37	13.12
1605	36	23.23	23.23	16.59
1605	40	28.78	28.78	20.56
1605	44	34.69	34.69	24.78
1605	48	41.37	41.37	29.55

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved