



## Swivel

### Product information

**General:** Swivels are essential for the safe and efficient installations of cables, both over and underground. Ball bearing swivels stop torque gradually building by both the pulling equipment and the lay of the cables themselves. The swivels are contoured to allow ease of passage through pulley sheaves. Swivels are an indispensable aid for safe and easy cable laying. The use of double axial bearings makes it possible to neutralise the torsion as required, even under maximum tension.

**Material:** Stainless steel. Variant with BF 66.7 kN Alloy Steel

| Part code    | Min. breaking force<br>kN | Clevis gap<br>mm | A mm | B mm | C mm | D<br>mm | E<br>mm | F<br>mm | G<br>mm | Weight<br>kg |
|--------------|---------------------------|------------------|------|------|------|---------|---------|---------|---------|--------------|
| 492506400060 | 10                        | 7,1              | 16   | 7.1  | 4.8  | 17.5    | 6.4     | 51      | 64      | 0.06         |
| 492507800060 | 15                        | 7,1              | 20   | 7.1  | 4.8  | 22.6    | 8.7     | 61      | 78      | 0.12         |
| 492508600060 | 30                        | 9,5              | 22   | 9.5  | 7.9  | 24.6    | 11.1    | 64      | 86      | 0.15         |
| 492509500060 | 46.7                      | 10,3             | 25   | 10.3 | 9.5  | 27.8    | 12.7    | 73      | 98      | 0.23         |
| 492512100060 | 66.7                      | 13,5             | 32   | 13.5 | 10.3 | 32.5    | 13.5    | 94      | 121     | 0.45         |
| 492513000060 | 93.4                      | 14,3             | 35   | 14.3 | 12.7 | 35      | 15.9    | 98      | 130     | 0.63         |
| 492515240060 | 133.4                     | 17,5             | 41   | 17.5 | 15.9 | 43.7    | 19.1    | 114     | 152     | 0.95         |
| 492517800060 | 200.1                     | 19,8             | 51   | 19.8 | 17.5 | 52.4    | 23.8    | 130     | 178     | 1.7          |
| 492525400060 | 330                       | 26,2             | 60   | 26.2 | 22.2 | 70.6    | 30.2    | 202     | 262     | 3.5          |
| 492533000060 | 667                       | 30,2             | 76   | 20.2 | 28.6 | 98      | 44      | 260     | 349     | 7.7          |

## Blueprint

