

Samson wire rope blocks 2 sheave

Product information



General:

- Up to 30 ton blocks standard supplied with swivel oval eye.
- Over 30 ton blocks standard supplied with swivel stud eye.
- Blocks can be supplied with swivel hook, swivel stud eye or swivel jaw on request.
- Standard supplied with bronze bearings. Other bearings available on request.
- Groove in sheave may be adjusted to other wire rope diameters on request.
- Blocks can be supplied with becket on request.

... [Read more](#)


Temperature range: -40°C / +80°C

Note: WLL= Working Load Limit on head fitting.

Safety factor: 4:1

Samson wire rope blocks 2 sheave

Blueprint



Technical data

| Part code | WLL ton | Rope Ø mm | No of Sheaves | Weight kg |
|--------------|---------|-----------|---------------|-----------|
| 424100100360 | 1 | 8 | 2 | 4 |
| 424100150360 | 1.5 | 10 | 2 | 6 |
| 424100300360 | 3 | 12 | 2 | 11 |
| 424100400360 | 4 | 14 | 2 | 18 |
| 424100600360 | 6 | 18 | 2 | 32 |
| 424100800360 | 8 | 20 | 2 | 43 |
| 424101000360 | 10 | 22 | 2 | 74 |
| 424101200360 | 12 | 22 | 2 | 81 |
| 424101200365 | 12 | 24 | 2 | 102 |
| 424101600360 | 16 | 22 | 2 | 98 |
| 424101600365 | 16 | 24 | 2 | 126 |
| 424102000360 | 20 | 22 | 2 | 116 |
| 424102000365 | 20 | 24 | 2 | 146 |
| 424102500360 | 25 | 24 | 2 | 169 |
| 424102500365 | 25 | 28 | 2 | 190 |
| 424103000360 | 30 | 24 | 2 | 184 |
| 424103000365 | 30 | 28 | 2 | 204 |
| 424104000360 | 40 | 28 | 2 | 225 |