

Samson wire rope blocks 2 sheave



Product information

General:

- Up to 30 ton blocks standard supplied with swivel oval eye.
- Over 30 ton blocks standard supplied with swivel stud eye.
- Blocks can be supplied with swivel hook, swivel stud eye or swivel jaw on request.
- Standard supplied with bronze bearings. Other bearings available on request.
- Groove in sheave may be adjusted to other wire rope diameters on request.
- Blocks can be supplied with becket on request.

Temperature range: -40°C / +80°C

Note: WLL= Working Load Limit on head fitting.

Safety factor: 4:1

Part code	WLL ton	Rope Ø mm	No of Sheaves	Weight kg
424100100360	1	8	2	4
424100150360	1.5	10	2	6
424100300360	3	12	2	11
424100400360	4	14	2	18
424100600360	6	18	2	32
424100800360	8	20	2	43
424101000360	10	22	2	74
424101200360	12	22	2	81
424101200365	12	24	2	102
424101600360	16	22	2	98
424101600365	16	24	2	126
424102000360	20	22	2	116
424102000365	20	24	2	146
424102500360	25	24	2	169
424102500365	25	28	2	190
424103000360	30	24	2	184
424103000365	30	28	2	204
424104000360	40	28	2	225

Blueprint

