

Samson wire rope blocks 3 sheave



Product information

General:

- Up to 30 ton blocks standard supplied with swivel oval eye.
- Over 30 ton blocks standard supplied with swivel stud eye.
- Blocks can be supplied with swivel hook, swivel stud eye or swivel jaw on request.
- Standard supplied with bronze bearings. Other bearings available on request.
- Groove in sheave may be adjusted to other wire rope diameters on request.
- Blocks can be supplied with becket on request.

Temperature range: -40°C / +80°C

Note: WLL= Working Load Limit on head fitting

Safety factor: 4:1

| Part code | WLL ton | Rope Ø mm | No of Sheaves | Weight kg |
|------------------|--------------------|----------------------|----------------------|----------------------|
| 424100200330 | 2 | 10 | 3 | 9 |
| 424100400330 | 4 | 12 | 3 | 17 |
| 424100600330 | 6 | 14 | 3 | 28 |
| 424100800330 | 8 | 18 | 3 | 46 |
| 424101000330 | 10 | 20 | 3 | 69 |
| 424101200330 | 12 | 22 | 3 | 99 |
| 424101600330 | 16 | 24 | 3 | 120 |
| 424101600335 | 16 | 24 | 3 | 157 |
| 424102000335 | 20 | 24 | 3 | 143 |
| 424102000330 | 20 | 24 | 3 | 184 |
| 424102500330 | 25 | 24 | 3 | 170 |
| 424102500335 | 25 | 24 | 3 | 198 |
| 424102500336 | 25 | 28 | 3 | 220 |
| 424103000330 | 30 | 28 | 3 | 215 |
| 424103000335 | 30 | 28 | 3 | 255 |
| 424104000330 | 40 | 28 | 3 | 250 |
| 424104000335 | 40 | 28 | 3 | 295 |
| 424105000330 | 50 | 28 | 3 | 335 |

Blueprint

