



Single Sheave Crane Blocks

Product information

General:

- Standard fitted with becket, cylindrical roller bearing and reeving guide.
- Standard fitted with Crosby type of swivel only hook (319AN style), including safety latch and split pin.
- Standard painted yellow (no striping).
- This crane block may be used with 2 lines only as well.
- Sheaves may be adjustud for other wire rope diameters.
- Becket suitable for connecting Open Wedge Socket for indicated wire rope.
- Becket can not be adjusted.

| Part code | WLL ton | Rope Ø mm | Sheave dia. mm | øD1 | øD2 | B, | O mm | S mm | TA mm | TB mm | TL mm | T mm | øZ | Weight kg |
|-----------------|---------|-----------|----------------|-----|-----|-----|------|------|-------|-------|-------|------|----|-----------|
| 6097HB2101115E | 5 | 11 | 250/210 | 250 | 210 | 348 | 34 | 30 | 320 | 103 | 523 | 20 | 27 | 41 |
| 6097HB2201315E | 5 | 13 | 260/221 | 260 | 221 | 353 | 34 | 30 | 353 | 109 | 525 | 22 | 27 | 67 |
| 6097HB2201418E | 8 | 14 | 260/218 | 260 | 218 | 390 | 43 | 35 | 330 | 121 | 571 | 28 | 32 | 80 |
| 6097HB2551318E | 8 | 13 | 300/255 | 300 | 255 | 426 | 43 | 30 | 370 | 101 | 621 | 22 | 27 | 89 |
| 6097HB2551618E | 8 | 16 | 300/252 | 300 | 252 | 420 | 43 | 35 | 370 | 111 | 621 | 28 | 32 | 94 |
| 6097HB25516110E | 10 | 16 | 300/252 | 300 | 252 | 459 | 52 | 35 | 370 | 127 | 659 | 28 | 32 | 91 |
| 6097HB22014110E | 10 | 14 | 260/218 | 260 | 218 | 429 | 52 | 35 | 330 | 137 | 609 | 28 | 32 | 93 |
| 6097HB30516110E | 10 | 16 | 350/305 | 350 | 305 | 499 | 52 | 35 | 435 | 107 | 739 | 28 | 33 | 113 |
| 6097HB34518112E | 12 | 18 | 400/345 | 400 | 345 | 557 | 57 | 45 | 500 | 125 | 832 | 35 | 37 | 162 |
| 6097HB39020116E | 16 | 20 | 450/390 | 450 | 390 | 592 | 57 | 50 | 550 | 131 | 917 | 35 | 43 | 206 |
| 6097HB43022120E | 20 | 22 | 500/430 | 500 | 430 | 592 | 76 | 50 | 600 | 148 | 1,032 | 40 | 43 | 284 |

Blueprint

