Lifting Solutions Group
Axel Johnson International

Lifting chain, grade 80

Product information

Short link lifting chain grade 80 is manufactured according to EN 818-2 standard.

... *Read more*



Material: Steel
Marking: According to standard
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, black
Standard: EN 818-2
Warning: Not to be heat-treated

Safety factor: 4:1
Grade: 8


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lifting chain, grade 80

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	A mm	B mm	D mm	Weight kg/m
2031NK6	6	1.12	18	9	6	0.8
2031NK8	8	2	24	12	8	1.35
2031NK10	10	3.15	30	14	10	2.15
2031NK13	13	5.3	39	19	13	3.5
2031NK16	16	8	48	23	16	5.5
2031NK20	20	12.5	60	25	20	8.4
2031NK22	22	15	66	28	22	10.35
2031NK26	26	21.2	78	35	26	15.8
2031NK32	32	31.5	96	43	32	23

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved