Shortening clutch sling hook, grade 80

Product information

Hook is equipped with spring loaded safety latch.

... *Read more*



Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-2
Warning: Not to be heat-treated

Safety factor: 4:1
Grade: 8


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Shortening clutch sling hook, grade 80

Blueprint



Technical data

Part code	WLL ton	For chain Ø mm	A mm	B mm	C mm	E mm	M mm	N mm	L mm	Ø mm mm	Weight kg
4013SALKH6TK	1.12	6	8	40	29	20	66	11	136	17	0.5
4013SALKH78TK	2	7/8	10	45	33	27	84	13	172	27	0.9
4013SALKH10TK	3.15	10	12	56	42	33	103	11	215	34	1.7
4013SALKH13TK	5.3	13	15	75	57	40	133	20	258	45	3.4
4013SALKH16TK	8	16	18.5	82	72	44	156.7	26.5	305	56	5.57

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved