CERTEX | Lifting Solutions Group
Axel Johnson International

Roundsling and webbing sling connector, grade 80.

Product information

Round sling and webbing sling connector is used for connecting short link grade 80 lifting chains to roundslings and webbing slings.

... *Read more*



Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-1
Warning: Not to be heat-treated

Safety factor: 4:1
Grade: 8


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Roundsling and webbing sling connector, grade 80.

Blueprint



Technical data

Part code	WLL ton	For chain Ø mm	W mm	B mm	A mm	K mm	E mm	Weight kg
4012PRL78	2	7/8	40	61	20	63	9	0.3
4012PRL10	3.15	10	39	66	24	83	11	0.68
4012PRL13	5.3	13	55	68	28	93	16	1.47
4012PRL16	8	16	65	88	34	120	19	2.3
4012PRL20	12.5	20	80	108	41	138	23	3.3

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved