

## Master link, grade 80

---

### Product information



Masterlink for chain sling assemblies.

[... Read more](#)

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-4


**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

## Master link, grade 80

### Blueprint



### Technical data

| Part code    | WLL ton | EWL mm | For chain, 1-leg mm | For chain, 2-leg mm | A mm | B mm | D mm | Weight kg |
|--------------|---------|--------|---------------------|---------------------|------|------|------|-----------|
| 401100160260 | 1.6     | 110    | 6/7                 | 6                   | 110  | 60   | 13   | 0.34      |
| 401100210260 | 2.12    | 110    | 8                   | 7                   | 110  | 60   | 16   | 0.53      |
| 401100320260 | 3.15    | 135    | 10                  | 8                   | 135  | 75   | 18   | 0.8       |
| 401100530260 | 5.3     | 160    | 13                  | 10                  | 160  | 90   | 22   | 1.5       |
| 401100800260 | 8       | 180    | 16                  | 13                  | 180  | 100  | 26   | 2.3       |
| 401101120260 | 11.2    | 200    | 18                  | 16                  | 200  | 110  | 32   | 3.9       |
| 401101400260 | 14      | 260    | 20                  | 18                  | 260  | 140  | 36   | 6.35      |
| 401101700260 | 17      | 300    | 22                  | 20                  | 300  | 160  | 40   | 9         |
| 401102120260 | 21.2    | 340    | 26                  | 22                  | 340  | 180  | 45   | 12.8      |
| 401103150260 | 31.5    | 350    | 32                  | 26                  | 350  | 190  | 50   | 17.2      |
| 401104500260 | 45      | 400    | 36                  | 32                  | 400  | 200  | 56   | 24.2      |