

## Master link, grade 80

---

### Product information



Masterlink for chain sling assemblies.

[... Read more](#)

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-4


**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

## Master link, grade 80

### Blueprint



### Technical data

Part code	WLL ton	EWL mm	For chain, 1-leg mm	For chain, 2-leg mm	A mm	B mm	D mm	Weight kg
401100160260	1.6	110	6/7	6	110	60	13	0.34
401100210260	2.12	110	8	7	110	60	16	0.53
401100320260	3.15	135	10	8	135	75	18	0.8
401100530260	5.3	160	13	10	160	90	22	1.5
401100800260	8	180	16	13	180	100	26	2.3
401101120260	11.2	200	18	16	200	110	32	3.9
401101400260	14	260	20	18	260	140	36	6.35
401101700260	17	300	22	20	300	160	40	9
401102120260	21.2	340	26	22	340	180	45	12.8
401103150260	31.5	350	32	26	350	190	50	17.2
401104500260	45	400	36	32	400	200	56	24.2