

Master link assemblies 3-4-I, grade 80

Product information



Masterlink for 3- and 4-leg chain sling assemblies.

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-4


Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Master link assemblies 3-4-I, grade 80

Blueprint



Technical data

Part code	WLL ton	EWL mm	For chain, 3-4-leg mm	L mm	B mm	D mm	B1 mm	D1 mm	L1 mm	Weight kg
401100240280	2.36	189	6	135	75	18	25	14	54	1.2
401100430280	4.25	230	7/8	160	90	22	34	16	70	2.2
401100670280	6.7	265	10	180	100	26	40	18	85	3.4
401101120280	11.2	315	13	200	110	32	50	22	115	6
401101700280	17	400	16	260	140	36	65	26	140	10
401102650280	26.5	500	20	350	190	51	70	32	150	23.3
401103200280	32	520	22	350	190	51	75	36	170	25.9
401104500280	45	570	26	400	200	57	80	40	170	35.2
401106700280	67	817	32	460	250	72	190	49	357	67.6