Lifting Solutions Group
Axel Johnson International

Lifting swivel with ball bearing, grade 80

Product information



Lubricated easily rotating swivels for use with lifting chains. Rotates easily also with full load. Equipped with large eye / eye ends.

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow/white
Standard: EN 1677-1
Note: Two models
Warning: Not to be heat-treated

Safety factor: 4:1


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lifting swivel with ball bearing, grade 80

Blueprint



Technical data

Part code	WLL ton	For chain Ø mm	b mm	c1 mm	c2 mm	d mm	t mm	Weight kg
4225LEIK6SS	1.12	6	32	33	33	12	126	0.61
4225LEIK78SS	2	7/8	37	40	40	14	153	1.07
4225LEIK10SS	3.2	10	39	35	65	19	168	1.5
4225LEIK13SS	5	13	61	65	100	28	258	3.4
4225LEIK16SS	8.2	16	73	67	67	17	281	6.44
4225LEIK18SS	12.8	18-20	82	88	88	25	328	7.75

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved