Latch hook with swivel, grade 80

Product information



Hook is equipped with spring loaded safety latch. Due to the swivel the hook is easy to align into the wanted direction.

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-2
Warning: Not to be heat-treated

Safety factor: 4:1
Grade: 8


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Latch hook with swivel, grade 80

Blueprint



Technical data

Part code	WLL ton	EWL mm	For chain Ø mm	K mm	E mm	A mm	B mm	Weight kg
4013SALKL6	1.12	138	6	170	22	32.5	22	0.34
4013SALKL78	2	167	7/8	210	27	35.5	26	0.85
4013SALKL10	3.15	197	10	247	32	42	34	1.54
4013SALKL13	5.3	247	13	302	40	50	38.5	3.4
4013SALKL16	8	305	16	382	45	61	55	5.36
4013SALKL20	12.5	336	20	418	49	72	61	7.4
4013SALKL22	15	433	22	527	54	95	95	10.6
4013SALKL26	21.2	510	26	610	81	122	115	21.4

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved