

Foundry eye hook, grade 80

Product information



Foundry eye hook with a wide mouth opening are attached to the chain with connecting slings.

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-1


Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Foundry eye hook, grade 80

Blueprint



Technical data

Part code	WLL ton	EWL mm	For chain Ø mm	P mm	H mm	K mm	D mm	A mm	M mm	Weight kg
401300110620	1.12	124	6	62	29	163	17	39	26	1
401300200620	2	122	7/8	63	31	163	18	39	25	1.09
401300320620	3.15	150	10	76	38	200	22	50	32	2.04
401300530620	5.3	180	13	89	44	238	27	63	38	3.22
401300800620	8	210	16	102	52	278	32	76	46	5.53
401301250620	12.5	240	20	114	65	325	38	89	55	8.75
401301500620	15	272	22	127	69	361	45	102	57	11.93
401302120620	21.2	302	26	140	77	402	67	126	66	16.8
401303150620	31.5	340	32	153	97	461	81	151	80	26.6