

Starcon Double Headed Anchors



Product information



The STARCON double headed anchor is a steel component made for concrete casting.

The foot of the anchor is constructed especially for strong concrete anchorage.

The cylindrical head of the STARCON double headed anchor is attached to a STARCON lifting eye for lifting.

Material: Steel S355.

Marking: According to standard, Load group+S, batch code, CE

Temperature range: 200°C.

Finish: Black or hot dip galvanized.

Standard: CEN/TR 15728 - VDI/BV-BS 6205

Part Code	Size	I mm	D mm	D2 mm	k mm	Da mm	Weight kg
99.101010405E	40	40	10	25	10	60	0.04
99.101010655E	65	65	10	25	10	60	0.06
99.101011250E	120	120	10	25	10	60	0.11
99.101012405E	240	240	10	25	10	60	0.18

Technical data

Load group 2.5

Art No	l	d	d2	k	Da	Weight
Black	mm	mm	mm	mm	mm	kg
99.101030855E	85	14	35	11	74	0,16
99.101031250E	120					0,21
99.101031750	170					0,27

Load group 5.0

Art No	l	d	d2	k	Da	Weight
Black	mm	mm	mm	mm	mm	kg
99.101050904EE	90	20	50	15	94	0,40
99.101051104E	110					0,43

Blueprint

