



STA-SA Universal and Erection Anchor Conical

Product information

The Transport Anchor STA-SA - CONIC is suitable for loads from 0.7 up to 22.0 t. The conical transport anchor is designed for the tipping of panels from a horizontal to a vertical position. The conical anchor is used for erection and turning of precasted thin wall units in both directions. The head of the anchor has a hole in which the locking bolt of the lifting eye is mounted. Other holes in the anchor are meant for further reinforcement. The head of the anchor is designed so that the load cannot be transferred to the upper part of the concrete surface.

Surface: Black or hot dip galvanized.

Material: Steel S355.

Marking: According to standard, CE-marked, Load group + Starcon, batch code

Temperature range: 200°C

Standard: CEN/TR 15728 - VDI/BV-BS 6205

Part Code	WLL ton	b mm	c mm	d mm	l mm	Weight kg
99.15TPASA0142000	1.4	50	6	15	200	0.38
99.15TPASA0252300	2.5	50	10	15	230	0.674
99.15TPASA0502900	5	70	15	20	290	1.894
99.15TPASA1255000	12.5	150	20	35	500	6.438
99.15TPASA1705000	17	150	25	35	500	6.82
99.15TPASA2205000	22	150	30	36	500	9.96

Blueprint

