



Clevis Shackle X-066, painted grade 100 shackle

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C.
- Magnaflux crack detection is performed 100% on each batch.
- Manufactured in accordance with EN 1677- 1 and ASME B30.26.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, Size, grade, manufacturer ID, traceability

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted

Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

Part Code	Chain diameter mm	WLL ton	A mm	C mm	G mm	K mm	L mm	M mm	W mm	Weight kg
42050472B	7-8	2.5	9	79	34	59	35	16	33	0.4
42050473B	10	4	11	93	40	78	48	20	37	0.8
42050474B	13	6.7	14	118	44	98	64	22	49	1.4
42050475B	16	10	18	141	54	112	69	28	60	2.5

Blueprint

