Lifting Solutions Group
Axel Johnson International

Clevis Foundry Hook X-046 Grade 10

Product information



At least 25% greater WLL than traditional Grade 8 products.
Testing according to DIN PAS 1061 and ASTM A952/A 952M.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
Tempering temperature minimum 400°C.
Designed for the assembly of chain slings where wide throat openings are necessary.

... *Read more*

Material: Quenched and tempered alloy steel.
Marking: According to standard, Size, grade, manufacturer ID, traceability.
Temperature range: -40ºC up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-1
Warning: Before using the hook, check whether hooks without safety latches are allowed to be used for the particular application.

Safety factor: 4:1
Grade: 10


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Clevis Foundry Hook X-046 Grade 10

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	EWL mm	A mm	H mm	K mm	P mm	T mm	Weight kg
402300250770	7-8	2.5	133	9	27	133	62	19	0.95
402300400770	10	4	163	11	32	163	74	23	1.8
402300670770	13	6.7	200	14	39	200	88	32	3.6

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved