



## Clevis Sling Hook X-043/S Grade 10

### Product information

At least 25% greater WLL than traditional Grade 8 products.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.

Tempering temperature minimum 400°C.

Magnaflux crack detection is performed 100% on each batch.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, Size, grade, manufacturer ID, traceability.

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-2

**Safety factor:** 4:1

**Grade:** 10

Part Code	WLL ton	For Grade 100 Chain mm	A mm	H mm	K mm	P1 mm	T mm	Weight kg
42050444B	1.4	6	7	18	79	23	15	0.3
42050445B	2.5	7, 8	9	22	98	27	18	0.6
42050446B	4	10	12	30	122	34	24	1.1
42050447B	6.7	13	15	37	147	44	30	2.3
42050448B	10	16	17	41	166	48	39	3.8
42050449B	16	20	24	64	207	57	48	8.7
42050450B	19	22	25	61	217	73	52	9.5

## Blueprint

