



## Swivel Self Locking Hook X-027N

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Rotate when loaded.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Built with ball bearing and enables full swivel feature under load.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard

**Temperature range:** Tempering temperature minimum 400°C .

**Finish:** Blue painted.

**Standard:** EN 1677-3

**Safety factor:** 4:1

**Grade:** 10

Part Code	Chain diameter mm	WLL ton	A mm	B mm	D mm	H mm	K mm	P mm	T mm	Weight kg
42050409B	6	1.4	32	23	12	19	149	28	15	0.7
42050410B	7-8	2.5	36	29	13	24	186	34	20	1.2
42050411B	10	4	41	35	16	30	218	44	26	2
42050412B	13	6.7	46	44	21	39	276	51	30	4.1
42050413B	16	10	61	50	23	49	329	60	36	7.2
42050414B	20	16	74	82	25	65	403	70	53	13
42050415B	22	19	97	96	33	63	454	80	49	20
42050416B	26	26.5	123	116	51	69	535	99	56	33

Blueprint

