



Clevis Grip Safe Locking Hook X-951

Product information

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL. Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard

Temperature range: Tempering temperature minimum 400°C

Standard: EN 1677-3

Safety factor: 4:1

Grade: 10

| Part Code | Chain diameter mm | WLL ton | A mm | H mm | K mm | O mm | P mm | T mm | W mm | Weight kg |
|-----------|----------------------|------------|---------|---------|---------|---------|---------|---------|---------|--------------|
| 42050494B | 10 | 4 | 12.1 | 31 | 153 | 49 | 71 | 27 | 137 | 1.9 |
| 42050495B | 13 | 6.7 | 15.5 | 39 | 203 | 64 | 80 | 34 | 174 | 4.1 |
| 42050496B | 16 | 10 | 19.1 | 47 | 244 | 78 | 114 | 39 | 212 | 7.1 |
| 42050497B | 20 | 16 | 24 | 55 | 312 | 92 | 127 | 54 | 251 | 12.7 |
| 42050498B | 22 | 20 | 24.2 | 59 | 304 | 98 | 151 | 56 | 258 | 14.1 |

Blueprint

