



Eye Grip Safe Locking Hook X-950

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Avoid finger injury by the grip design.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-3

Safety factor: 4:1

Grade: 10

Part Code	Chain diameter mm	WLL ton	A mm	D mm	H mm	K mm	O mm	P mm	T mm	W mm	Weight kg
42050489B	10	4	33	13	31	176	49	71	27	137	1.9
42050490B	13	6.7	40	16	39	226	64	80	34	174	4
42050491B	16	10	50	21	47	277	78	114	39	212	6.3
42050492B	20	16	62	23	55	329	92	127	54	251	12.3
42050493B	22	19	70	24	59	350	98	151	56	258	14

Blueprint

