



Clevis Grab Hook X-042

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Testing according to DIN PAS 1061 and ASTM A952/A 952M.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Enables full WLL while in use, thanks to supporting wings which prevent chain link deformation.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Standard: EN 1677-1

Warning: Not for use with Omega Link

Safety factor: 4:1

Grade: 10

Part Code	Chain diameter mm	WLL ton	A mm	F mm	H mm	K mm	L mm	P mm	Weight kg
42050437B	6	1.4	7	25	18	47	79	8	0.2
42050438B	7-8	2.5	10	30	22	54	93	10	0.4
42050439B	10	4	11	41	29	77	128	13	0.8
42050440B	13	6.7	15	52	38	99	165	17	1.6
42050441B	16	10	18	57	45	114	195	21	2.7
42050442B	20	16	22	73	52	130	222	23	4.8
42050443B	22	19	24	70	56	139	247	26	6.4

Blueprint

