

## Shackles, SAE - bow model

---

### Product information



Shackles approved for lifting. Bow shackles are suitable for use when more than one attachment is to be made to the body (multi-leg systems), or to allow freedom of movement in the plane of the bow. Screw pin shackles are easily manipulated. They are typically suitable for non-permanent applications and one-off installations, when there is no tendency for the pin to unscrew and the shackle can be observed under operation.

... [Read more](#)

---

**Features:** RFID-ready

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C - (+)200°C


**Finish:** Hot dip galvanized

**Standard:** US. FED. SPEC. RR-C-271F

**Safety factor:** 6:1

## Shackles, SAE - bow model

### Blueprint



### Technical data

Part code	WLL ton	Size inch	A mm	B mm	C mm	D, mm	E mm	F mm	G, mm	H, mm	I mm mm	Mmm mm	Nmm mm	Weight kg
420100030690	0.33	3/16	10	7	22	5	15	14	25	38	4	29	5	0.03
420100050690	0.5	1/4	12	8	29	7	20	16	33	47	5	35	5	0.05
420100750690	0.75	5/16	14	10	31	8	22	19	38	53	6	42	8	0.09
420100100690	1	3/8	17	11	37	10	26	23	45	63	7	52	10	0.14
420100150690	1.5	7/16	19	13	43	11	30	27	52	74	8	61	11	0.17
420100200690	2	1/2	21	16	48	13	34	30	59	84	10	69	13	0.33
420100330690	3.25	5/8	27	19	61	16	43	38	75	106	11	85	18	0.62
420100480690	4.75	3/4	32	23	72	19	51	46	89	126	13	101	21	1.07
420100650690	6.5	7/8	37	26	84	23	58	53	102	148	13	114	25	1.64
420100850690	8.5	1	43	29	96	26	69	61	119	167	14	129	27	2.28
420100950690	9.5	1-1/8	46	32	108	30	74	69	131	190	16	142	32	3.36
420101200690	12	1-1/4	52	35	119	33	93	76	146	210	18	156	35	4.31
420101350690	13.5	1-3/8	57	38	133	36	92	84	162	233	19	174	38	6.14
420101700690	17	1-1/2	61	42	146	39	99	92	175	254	21	187	41	7.8
420102500690	25	1-3/4	73	51	178	47	127	106	225	313	26	231	57	12.6
420103500690	35	2	83	57	197	53	146	122	253	348	31	263	61	20.4
420105500690	55	2-1/2	105	70	267	69	184	145	327	453	35	330	80	38.9
420108500690	85	3	127	82	330	76	200	165	367	546	38	490	105	70