



Single webbing slings 1 - 5 t

Product information

Single layer lifting slings. The width of the sling is high with respect to the workload. Perfect for places, where minimal surface pressure on the load to be lifted is needed, for example when lifting boats. Folded reinforced eyes as standard and also available with flat eyes.

Thanks to our own production unit, we can also make quick deliveries of special types and lengths as well as lifting slings with higher WLL.

Features: RFID-ready

Material: 100% polyester

Marking: CE-marked

Temperature range: -40°C - +100 °C

Note: Color coded

Warning: Standard dimensional tolerance is $\pm 3\%$. Lengths can vary within the tolerance range!

Safety factor: 7:1

Part code	WLL ton	EWL m	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	Webbing width mm	Colour
341100100100310	1	1	0.8	2	1.4	1	60	Green
341100100200310	1	2	0.8	2	1.4	1	60	Green
341100100300310	1	3	0.8	2	1.4	1	60	Green
341100100400310	1	4	0.8	2	1.4	1	60	Green
341100100500310	1	5	0.8	2	1.4	1	60	Green
341100100600310	1	6	0.8	2	1.4	1	60	Green
341100100800310	1	8	0.8	2	1.4	1	60	Green
341100101000310	1	10	0.8	2	1.4	1	60	Green

341100101200310	1	12	0.8	2	1.4	1	60	Green
341100101400310	1	14	0.8	2	1.4	1	60	Green
341100200100310	2	1	1.6	4	2.8	2	120	Grey
341100200200310	2	2	1.6	4	2.8	2	120	Grey
341100200300310	2	3	1.6	4	2.8	2	120	Grey
341100200400310	2	4	1.6	4	2.8	2	120	Grey
341100200500310	2	5	1.6	4	2.8	2	120	Grey
341100200600310	2	6	1.6	4	2.8	2	120	Grey
341100200800310	2	8	1.6	4	2.8	2	120	Grey
341100201000310	2	10	1.6	4	2.8	2	120	Grey
341100201200310	2	12	1.6	4	2.8	2	120	Grey
341100201400310	2	14	1.6	4	2.8	2	120	Grey
341100300200310	3	2	2.4	6	4.2	3	180	Brown
341100300300310	3	3	2.4	6	4.2	3	180	Brown
341100300400310	3	4	2.4	6	4.2	3	180	Brown
341100300500310	3	5	2.4	6	4.2	3	180	Brown
341100300600310	3	6	2.4	6	4.2	3	180	Brown
341100300800310	3	8	2.4	6	4.2	3	180	Brown
341100301000310	3	10	2.4	6	4.2	3	180	Brown
341100301200310	3	12	2.4	6	4.2	3	180	Brown
341100301400310	3	14	2.4	6	4.2	3	180	Brown
341100400200310	4	2	3.2	8	5.6	4	240	Blue
341100400300310	4	3	3.2	8	5.6	4	240	Blue

341100400400310	4	4	3.2	8	5.6	4	240	Blue
341100400500310	4	5	3.2	8	5.6	4	240	Blue
341100400600310	4	6	3.2	8	5.6	4	240	Blue
341100400800310	4	8	3.2	8	5.6	4	240	Blue
341100401000310	4	10	3.2	8	5.6	4	240	Blue
341100401200310	4	12	3.2	8	5.6	4	240	Blue
341100401400310	4	14	3.2	8	5.6	4	240	Blue
341100500300310	5	3	4	10	7	5	300	Orange
341100500400310	5	4	4	10	7	5	300	Orange
341100500500310	5	5	4	10	7	5	300	Orange
341100500600310	5	6	4	10	7	5	300	Orange
341100500800310	5	8	4	10	7	5	300	Orange
341100501000310	5	10	4	10	7	5	300	Orange
341100501200310	5	12	4	10	7	5	300	Orange
341100501400310	5	14	4	10	7	5	300	Orange