



Round slings assemblies 4-legs

Product information

Lighter alternative to a chain combination in, for example, transformer lifting without risk of insulator damage etc. Also available with self-locking hooks, rotating swivel hooks, shackles etc.

Features: RFID-ready

Material: 100% polyester

Marking: CE-marked

Temperature range: -40°C - +100 °C

Safety factor: 4:1

Part code	WLL ton	WLL 0-45° t	WLL 45-60° t	Length m
3403	2.1	2.1	1.5	1
3403	2.1	2.1	1.5	1.5
3403	2.1	2.1	1.5	2
3403	2.1	2.1	1.5	2.5
3403	2.1	2.1	1.5	3
3403	2.1	2.1	1.5	4
3403	4.2	4.2	3.0	1
3403	4.2	4.2	3.0	1.5

3403	4.2	4.2	3,0	2
3403	4.2	4.2	3,0	2.5
3403	4.2	4.2	3,0	3
3403	4.2	4.2	3,0	4
3403	6.3	6.3	4,5	1
3403	6.3	6.3	4,5	1.5
3403	6.3	6.3	4,5	2
3403	6.3	6.3	4,5	2.5
3403	6.3	6.3	4,5	3
3403	6.3	6.3	4,5	4
3403	10.5	10.5	7,5	1
3403	10.5	10.5	7,5	1.5
3403	10.5	10.5	7,5	2
3403	10.5	10.5	7,5	2.5
3403	10.5	10.5	7,5	3
3403	10.5	10.5	7,5	4
3403	17	17	11,8	2
3403	17	17	11,8	2.5
3403	17	17	11,8	3
3403	17	17	11,8	4
3403	17	17	11,8	5
3403	17	17	11,8	6