



## Lifting Belt Sling

### Product information

The Lift-Tex® lifting belt sling is a wide-body lifting sling designed for handling heavy loads up to 100 tonnes. It is used in applications where increased surface contact, load stability, and reduced wear are critical. Manufactured from HMPE and polyester, it combines high strength with controlled load distribution for demanding lifting operations.

WLL range: 10t – 100t  
EWL range: 0,5m – 65m

#### When to choose this product

##### Best for:

- Lifting heavy loads requiring increased surface contact and stability
- Applications where reduced surface pressure and sling wear are important

#### Product benefits

- Wide body design improves load distribution and lifting stability
- HMPE and polyester core delivers high strength and durability
- Reinforced soft eyes support secure and efficient hook connection
- Optional protective sleeves increase resistance to cuts and abrasion
- Multi-channel construction enhances control during lifting operations

**Material:** HMPE and Polyester

**Marking:** According to standard, Label in a reinforced plastic seal.

**Standard:** EN 1492-1

**Standard:** EN 1492-2

*except material*

**Safety factor:** 7:1

| Part code       | WLL<br>ton | Width<br>mm | Eye length<br>mm | Colour |
|-----------------|------------|-------------|------------------|--------|
| 342101000000020 | 10         | 240-260     | 700              | Orange |
| 342101500000020 | 15         | 240-260     | 700              | Orange |
| 342102000000020 | 20         | 350-400     | 700              | Orange |
| 342102500000020 | 25         | 350-400     | 700              | Orange |
| 342103000000020 | 30         | 350-400     | 700              | Orange |
| 342104000000020 | 40         | 450-500     | 700              | Orange |
| 342105000000020 | 50         | 450-500     | 700              | Orange |