Lifting Solutions Group
Axel Johnson International

Electric Chain Hoist KITO ER2 Large Capacity Single Speed Series

Product information



Electric chain hoist with hook suspension

General: The KITO ER2 Electric Chain Hoists are durable, safe and easy to use hoists. It has a top hook or overhead mounting suspension, aluminium die-cast body, electromagnetic brake and a canvas chain container.
It lifts from 10 tons up to 20 tons.

Standard configuration:

- 400 V/50 Hz
- Contactor control for single speed
- CH-Meter: operating hours/number of starts
- Ergonomic push button control
- Upper-lower limit switch
- Nickel-plated load chain class grade 80 (DAT) in accordance with Norm EN 818-7
- Thermal protector
- Carbon friction clutch

Options:

- 500 V/Contactor control
- 230 V/50 Hz/60 Hz, 3 phase
- Rubber bumpers for motorized trolleys
- Additional mechanical brake
- Electrical overload limiter
- Acoustic overload signal

... *Read more*

Standard preconfigured hoist (lifting height 3m, pendant control cable 2,5m)


Certex Polska
info@certex.pl
+48 91 817 28 49

© October 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Electric Chain Hoist KITO ER2 Large Capacity Single Speed Series

Blueprint



Technical data

Code	WLL ton	Number of falls	Motor kW	Lifting motor Rating (%ED)	Lifting speed* 50Hz m/min	Class ISO/FEM	Additional weight per 1 m lift	Load chain mm	Weight kg
ER2-1005	10	4	3.5x2	60	2,9	M4/1Am	11	11,2 x 31,3	303
ER2-1505	15	6	3.5x2	60	1,9	M4/1Am	17	11,2 x 31,3	404
ER2-2005	20	8	3.5x2	60	1,4	M4/1Am	22	11,2 x 31,3	476

Dimensions

WLL	Product	Min. headroom C	D	a	b	w	g
tons	code	mm	mm	mm	mm	mm	mm
10	ER2-100S	1370	1210	798	849	956	80
15	ER2-150S	1595	1520	798	1022	1129	86
20	ER2-200S	1710	1600	798	1198	1305	102

Certex Polska
info@certex.pl
+48 91 817 28 49

© October 2026 - All Rights Reserved