



## Electric Chain Hoist KITO ER2 Large Capacity Single Speed Series

### Product information

#### Electric chain hoist with hook suspension

**General:** The KITO ER2 Electric Chain Hoists are durable, safe and easy to use hoists. It has a top hook or overhead mounting suspension, aluminium die-cast body, electromagnetic brake and a canvas chain container. It lifts from 10 tons up to 20 tons.

#### Standard configuration:

- 400 V/50 Hz
- Contactor control for single speed
- CH-Meter: operating hours/number of starts
- Ergonomic push button control
- Upper-lower limit switch
- Nickel-plated load chain class grade 80 (DAT) in accordance with Norm EN 818-7
- Thermal protector
- Carbon friction clutch

#### Options:

- 500 V/Contactor control
- 230 V/50 Hz/60 Hz, 3 phase
- Rubber bumpers for motorized trolleys
- Additional mechanical brake
- Electrical overload limiter
- Acoustic overload signal
- Radio remote control
- Variable speed control
- Level limit switch
- Steel chain container
- Trolley versions: motorized, geared and plain

**Standard preconfigured hoist (lifting height 3m, pendant control cable 2,5m)**

Code	WLL ton	Number of falls	Motor kW	Lifting motor Rating (%ED)	Lifting speed* 50Hz m/min	Class ISO/FEM	Additional weight per 1 m lift	Load chain mm	Weight kg
ER2-1005	10	4	3.5x2	60	2,9	M4/1Am	11	11,2 x 31,3	303
ER2-1505	15	6	3.5x2	60	1,9	M4/1Am	17	11,2 x 31,3	404
ER2-2005	20	8	3.5x2	60	1,4	M4/1Am	22	11,2 x 31,3	476

## Technical data

### Dimensions

WLL	Product	Min. headroom C	D	a	b	w	g
tons	code	mm	mm	mm	mm	mm	mm
10	ER2-100S	1370	1210	798	849	956	80
15	ER2-150S	1595	1520	798	1022	1129	86
20	ER2-200S	1710	1600	798	1198	1305	102

# Blueprint

