Lifting Solutions Group
Axel Johnson International

Spreader with multiple hook positioning

Product information



General: The spreaders have a high point of oscillation which results in good balance. The table only shows a few examples of available sizes and provide an indication of dimensions, loads and weights. Other lengths and working loads can be manufactured to suit a customers requirements. All spreaders are supplied complete with 2-leg sling and shackles according to the table. The beams can be provided with other accessories such as hooks, wire rope slings, chain slings or textile slings. Please also refer to our description in the introduction to this section on lifting beams.
Design: Lightweight welded pipe beam construction providing good torsional stiffness.

Proof: 1,5 x WLL.

... *Read more*

Material: Hollow beam and plate manufactured with high-strength structural steel.
Marking: Working load limit and CE marking.
Finish: Yellow painted.

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Spreader with multiple hook positioning

Technical data

Part code	WLL ton	Length m	WLL t
6205	2	1-6	-
6205	4	1-6	-
6205	6	1-6	-
6205	10	1-6	-
6205	15	1-6	-
6205	20	1-6	-
6205	25	1-6	-
6205	-	1-6	>25 Ton

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved