



Anchor Starcon Load Group 10 t

Product information

The Starcon spherical head anchor load group 10 t is a steel component made for concrete casting. The foot of the anchor is constructed especially for strong concrete anchorage.

The cylindrical head of the Starcon spherical anchor is attached to a Starcon Lifting eye, standard coupling lifting eye for lifting.

Starcon refers to the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

Finish: Untreated, hot dip galvanized or stainless

Part Code	Load grp.	Length mm	Finish	D mm	D1 mm	D2 mm	L mm	Weight kg
99.101101500	10.0t	150	Untreated	28	47	70	150	1.09
99.101101502	10.0t	150	HDG	28	47	70	150	1.09
99.101101700	10.0t	170	Untreated	28	47	70	170	1.18
99.101101702	10.0t	170	HDG	28	47	70	170	1.18
99.101102200	10.0t	220	Untreated	28	47	70	220	1.44
99.101102202	10.0t	220	HDG	28	47	70	220	1.44
99.101102500	10.0t	250	Untreated	28	47	70	250	1.56
99.101102502	10.0t	250	HDG	28	47	70	250	1.56
99.101103400	10.0t	340	Untreated	28	47	70	340	1.98
99.101103402	10.0t	340	HDG	28	47	70	340	1.98
99.101106800	10.0t	680	Untreated	28	47	70	680	3.57
99.101106802	10.0t	680	HDG	28	47	70	680	3.57

Blueprint

