



Anchor Starcon Load Group 2.5 t

Product information

The Starcon spherical head anchor load group 2,5 t is a steel component made for concrete casting. The foot of the anchor is constructed especially for strong concrete anchorage.

The cylindrical head of the Starcon spherical anchor is attached to a Starcon Lifting eye, standard coupling lifting eye for lifting.

Starcon refers to the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, UKCA-marked, Batch code, Load group+S (Starcon)

Finish: Untreated, hot dip galvanized or stainless

Part Code	Load grp.	Length mm	Finish	D mm	D1 mm	D2 mm	L mm	Weight kg
99.101030450	2.5t	45	Untreated	14	26	35	45	0.12
99.101030452	2.5t	45	HDG	14	26	35	45	0.12
99.101030550	2.5t	55	Untreated	14	26	35	55	0.13
99.101030552	2.5t	55	HDG	14	26	35	55	0.13
99.101030680	2.5t	68	Untreated	14	26	35	68	0.15
99.101030682	2.5t	68	HDG	14	26	35	68	0.15
99.101030850	2.5t	85	Untreated	14	26	35	85	0.17
99.101030852	2.5t	85	HDG	14	26	35	85	0.17
99.101031200	2.5t	120	Untreated	14	26	35	120	0.21
99.101031202	2.5t	120	HDG	14	26	35	120	0.21
99.101031400	2.5t	140	Untreated	14	26	35	140	0.23
99.101031402	2.5t	140	HDG	14	26	35	140	0.23
99.101031700	2.5t	170	Untreated	14	26	35	170	0.27
99.101031702	2.5t	170	HDG	14	26	35	170	0.27
99.101032800	2.5t	280	Untreated	14	26	35	280	0.4
99.101032802	2.5t	280	HDG	14	26	35	280	0.4

Blueprint

