



Anchor Starcon Load Group 20 t

Product information

The Starcon spherical head anchor load group 20 t is a steel component made for concrete casting. The foot of the anchor is constructed especially for strong concrete anchorage.

The cylindrical head of the Starcon spherical anchor is attached to a Stardon Lifting eye, standard coupling lifting eye for lifting.

Starcon refers to the guidelines in VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, UKCA-marked, Batch code, Load group+S (Starcon) Finish: Untreated, hot dip galvanized or stainless

Part Code	Load grp.	Length mm	Finish	D mm	D1 mm	D2 mm	L mm	Weight kg
99.101202500E	20.0t	250	Untreated	39	70	98	250	3.3
99.101202502E	20.0t	250	HDG	39	70	98	250	3.3
99.101203400	20.0t	340	Untreated	39	70	98	340	4.38
99.101203402	20.0t	340	HDG	39	70	98	340	4.38
99.101205000E	20.0t	500	Untreated	39	70	98	500	5.87
99.101205002E	20.0t	500	HDG	39	70	98	500	5.87
99.101210000	20.0t	1,000	Untreated	39	70	98	1,000	11.75
99.101210002	20.0t	1,000	HDG	39	70	98	1,000	11.75

Blueprint

