

Crane Lift Basket BK-500 / BK-1000 / BK-1000 (Emergency)

Product information



Man riding baskets can be used quickly and safely for temporary working at heights. Our man riding baskets are designed to be hung from a crane hook.

If the basket is exposed to corrosive environment, we recommend additional treatment according to Offshore coating system.

Storage: For increased longevity, we recommend that the basket is stored in-doors in a dry environment."

Design: Welded frame in hollow beam with the bottom and sides covered in expanded-metal mesh. Personal items of safety equipment can be attached to the inside handrail. The basket is supported underneath for easy handling by truck or forklift. A gate is provided on one of the short sides (see the respective model). The basket is supplied complete with a four leg wire rope sling and a masterlink type MLA.

BK-500: Supplied with inward-opening latching gate.

BK-1000: Supplied with inward-opening latching gate.

BK-1000E (Emergency): Identical to the BK-500 / BK-1000 above except that in an emergency the entire end gate can be opened outwards to provide access, eg, for a stretcher and medical equipment to be taken on board.

Material: Hollow-beam and plate of high-strength structural steel.

Marking: Sign according to standard for inspection mark.

Finish: Yellow protective painting, RAL 1003, corrosivity class C3 (indoor storage), other painting programs are quoted upon request.

| Part code | Code | WLL ton | Basket weight kg | Max. number of persons | A mm | B mm | E mm | H mm | L mm | Weight kg |
|-------------|----------|------------|---------------------|------------------------|-------|-------|---------|---------|---------|--------------|
| 6211BK0500 | BK-500 | 0.5 | 220 | 2 | 1,240 | 1,000 | 600 | 2,000 | 3,100 | 720 |
| 6211BK1000 | BK-1000 | 1 | 350 | 4 | 2,000 | 1,200 | 700 | 2,100 | 4,470 | 1,350 |
| 6211BK1000E | BK-1000E | 1 | 400 | 4 | 2,300 | 1,200 | 700 | 2,100 | 4,700 | 1,400 |

Blueprint

