



## Vari Pump - 230V - 2 Stage W

### Product information

Holmatro Vari Pump units

**To control your hydraulic system, Holmatro offers a various range of pump units:**

- 230V, 400V or petrol driven
- 1 or 2 stage

**Unique specifications:**

- In case of a power failure, the oil pressure is maintained
- Protected against pressure drop by pressure-controlled non-return valve
- Excluding single-acting (M311) or double-acting (M322 or M323) control valve
- TIP: If you want to create flexibility for feature use; ad a Sada switch (M304) to your pump set-up

You want to make sure you choose the right vari-pump for your application? Download the Holmatro Vari pump configurator.

**Additional information:**

To have a safe and controlled system, assemble your vari-pump with advised components:

- Option A: 1 cylinder application : assemble a pressure gauge directly on the pump unit
- Option B: multiple cylinder application: add a flow panel & assembly set to your pump set-up
- TIP: download the vari-pump configurator for more info

**Why add a pressure gauge or flowpanel?**

- To measure the pressure in the system; safety first
- Go here for the valves & accessories for Holmatro vari pumps

**Also available:**

- Hydraulic cylinders 700 bar
- Hydraulic hoses 700bar
- System components to complete your hydraulic system
- Other hydraulic pump units 700bar to control the cylinder(s)

**Features:** - Safe; in case of a power failure, the oil pressure is maintained.

**Note:** Excluding single-acting or double-acting control valve.

Part Code	Code	max. working pressure bar/Mpa	oil capacity cc	Engine	Weight kg
45050316H	12 W 6 SD	720 / 72	6,000	230 VAC-1.5 kW-50 Hz-1 PH	40
45050309H	12 W 25 D	720 / 72	25,000	230 VAC-1.5 kW-50 Hz-1 PH	67
45050311H	12 W 50 D	720 / 72	50,000	230 VAC-1.5 kW-50 Hz-1 PH	96