



VARI Pump W - 230V - 2 Stage

Product information

Holmatro basic VARI Pump units. To control your hydraulic system, Holmatro offers a various range of pump units:

- 230V, 400V or petrol driven
- 1 or 2 stage

Unique specifications:

- In case of a power failure, the oil pressure is maintained
- Protected against pressure drop by pressure-controlled non-return valve
- Excluding single-acting (M311) or double-acting (M322 or M323) control valve
- TIP: If you want to create flexibility for feature use; ad a Sada switch (M304) to your pump set-up

You want to make sure you choose the right vari-pump for your application? Download the Holmatro Vari pump configurator.

Additional information:

To have a safe and controlled system, assemble your vari-pump with advised components:

- Option A: 1 cylinder application : assemble a pressure gauge directly on the pump unit
- Option B: multiple cylinder application: add a flow panel & assembly set to your pump set-up
- TIP: download the vari-pump configurator for more info

Why add a pressure gauge or flowpanel?

- To measure the pressure in the system; safety first
- Go here for the valves & accessories for Holmatro vari pumps

Also available:

- Hydraulic cylinders 700 bar
- Hydraulic hoses 700bar
- System components to complete your hydraulic system
- Other hydraulic pump units 700bar to control the cylinder(s)

Features: - Safe; in case of a power failure, the oil pressure is maintained.

Note: Excluding single-acting or double-acting control valve.

Part code	Code	Max. working pressure bar/Mpa	oil capacity cc	Engine	Weight kg
5201100152033	12 W 6 SD	720 / 72	6,000	230 VAC-1.5 kW-50 Hz-1 PH	40
5201100152035	12 W 25 D	720 / 72	25,000	230 VAC-1.5 kW-50 Hz-1 PH	67
5201100152036	12 W 50 D	720 / 72	50,000	230 VAC-1.5 kW-50 Hz-1 PH	96