



Horizontal Lifting Clamp IPH10(J)

Product information

The IPH10(J) horizontal lifting clamps with spring loaded tension have a pretension feature that allows the user to attach the clamps to the material for horizontal lifting and transfer of non-sagging material. These clamps must be used in pairs or more.

Features:

- Available in capacities of 0.5 through 12 metric tons.
- IPH10 type: jaw openings available: 0 to 60mm.
- IPH10J type: jaw openings available: 60 to 120mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Equipped with pretension system and handle for easy placement. Except 0.5t and 1t models.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

Material: Alloy steel

Marking: According to standard, CE-marked, WLL, Logo, Jaw opening, Serial number

Standard: EN 13155

Warning: To be used in pairs or more.

| Part code | WLL ton | Jaw width mm | Model | A, | B, | C, | E, | F, | G, | H, | J, | K, | L | Weight kg |
|-----------------|---------|--------------|------------|--------|-----|----|----|-----|-----|-----|----|----|----|-----------|
| 502100050200170 | 0.5 | 0-20 | 0.5-IPH10* | 0-20 | 86 | 12 | 16 | 103 | 150 | 60 | 12 | 27 | 4 | 1.8 |
| 502100100350170 | 1 | 0-35 | 1-IPH10* | 0-35 | 100 | 16 | 16 | 103 | 150 | 60 | 12 | 31 | 7 | 2.5 |
| 502100200600170 | 2 | 0-60 | 2-IPH10 | 0-60 | 117 | 16 | 22 | 109 | 256 | 110 | 20 | 40 | 9 | 5.5 |
| 502100300600170 | 3 | 0-60 | 3-IPH10 | 0-60 | 117 | 20 | 26 | 109 | 266 | 120 | 20 | 48 | 11 | 7.5 |
| 502100301200170 | 3 | 60-120 | 3-IPH10J | 60-120 | 177 | 20 | 26 | 109 | 266 | 120 | 20 | 48 | 11 | 9 |
| 502100450600170 | 4.5 | 0-60 | 4.5-IPH10 | 0-60 | 132 | 25 | 30 | 104 | 280 | 130 | 20 | 48 | 12 | 10.5 |
| 502100451200170 | 4.5 | 60-120 | 4.5-IPH10J | 60-120 | 192 | 25 | 30 | 104 | 280 | 130 | 20 | 48 | 12 | 12 |
| 502100600600170 | 6 | 0-60 | 6-IPH10 | 0-60 | 143 | 25 | 36 | 123 | 320 | 130 | 20 | 48 | 14 | 13 |
| 502100601200170 | 6 | 60-120 | 6-IPH10J | 60-120 | 203 | 25 | 36 | 123 | 320 | 130 | 20 | 48 | 14 | 15 |
| 502100900600170 | 9 | 0-60 | 9-IPH10 | 0-60 | 157 | 30 | 43 | 133 | 330 | 140 | 25 | 62 | 16 | 18.5 |
| 502100901200170 | 9 | 60-120 | 9-IPH10J | 60-120 | 217 | 30 | 43 | 133 | 330 | 140 | 25 | 62 | 16 | 20.5 |
| 502101200600170 | 12 | 0-60 | 12-IPH10 | 0-60 | 172 | 30 | 47 | 141 | 353 | 150 | 25 | 62 | 17 | 21.5 |
| 502101201200170 | 12 | 60-120 | 12-IPH10J | 60-120 | 232 | 30 | 47 | 141 | 353 | 150 | 25 | 62 | 17 | 24 |

Blueprint

