



## Zawory

Informacja o produkcie

Nr artykułu	Model	Opis
45050423H	A 109 N	• For accurate control of the oil flow, also under maximum pressure. • Connection: 3/8" NPT female (2x).
45050426H	A 195	• Very suitable for quick shut-off valve (open/close). • Can be operated under maximum pressure. • Connection: 3/8" NPT female (2x).
45050424H	A 130	• For accurate control of the oil flow, also under maximum pressure. • Connection: 3/8" NPT male and 3/8" NPT female.
45050427H	A 110	• Protects against sudden pressure drop in the supply pipe, for example in case of hose rupture. • To be mounted between pump and cylinder as close to the cylinder as possible. • Provided with pressure relief valve, set at 830 bars. • While pumping: valve closed, safety valve active. • For relief: open valve, safety valve not active. • Connection: 3/8" NPT female and 3/8" NPT male.
45050560H	A 134 N	• Suitable for hose rupture security. • Not to be used with double-acting systems. • Connection: 3/8" NPT, male. • Fits: A 119.
45050425H	A 209	• Spring-loaded. • Connection: 3/8" NPT male (2x).
45050421H	A 135	• Set to 750 bars. • Connection: 1x 3/8" NPT female and 1x 3/8" NPT male.