

## Chain Sling G80 4-leg with Foundry Hooks

### Product information

High quality 4-leg chain sling equipped with foundry hooks. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

**Marking:** According to standard, CE-marked

**Standard:** EN 818-4

**Safety factor:** 4:1

**Класс:** 8



Код товара	Chain diameter mm	WLL ton	EWL m	Вес kg
42071425W	6	2,36	0,5	17,77
42071430W	6	2,36	1	19,37
42071428W	6	2,36	1,5	20,97
42071437W	6	2,36	2	22,57
42071434W	6	2,36	2,5	24,17
42071443W	6	2,36	3	25,77
42071439W	6	2,36	3,5	27,37
42071446W	6	2,36	4	28,97

42071450W	6	2,36	5	32,17
42071454W	6	2,36	6	35,37
42071458W	8	4,25	0,5	22,194
42070215W	8	4,25	1	24,894
42071462W	8	4,25	1,5	27,594
42071466W	8	4,25	2	30,294
42071465W	8	4,25	2,5	32,994
42071470W	8	4,25	3	35,694
42071468W	8	4,25	3,5	38,394
42071472W	8	4,25	4	41,094
42071475W	8	4,25	5	46,494
42071479W	8	4,25	6	51,894
42071327W	10	6,7	0,5	25,16
42071335W	10	6,7	1	29,46
42071331W	10	6,7	1,5	33,76
42071338W	10	6,7	2	38,06
42071337W	10	6,7	2,5	42,36
42071343W	10	6,7	3	46,66
42071340W	10	6,7	3,5	50,96
42071344W	10	6,7	4	55,26
42071347W	10	6,7	5	63,86
42071350W	10	6,7	6	72,46
42071353W	13	11,2	0,5	44,23

42071361W	13	11,2	1	51,23
42071357W	13	11,2	1,5	58,23
42071368W	13	11,2	2	65,23
42071364W	13	11,2	2,5	72,23
42071374W	13	11,2	3	79,23
42071370W	13	11,2	3,5	86,23
42071375W	13	11,2	4	93,23
42071378W	13	11,2	5	107,23
42071382W	13	11,2	6	121,23
42071394W	16	17	1	71,07
42071390W	16	17	1,5	82,07
42071402W	16	17	2	93,07
42071398W	16	17	2,5	104,07
42071409W	16	17	3	115,07
42071405W	16	17	3,5	126,07
42071413W	16	17	4	137,07
42071417W	16	17	5	159,07
42071421W	16	17	6	181,07

## Blueprint

