

Chain Sling G80 2-leg with Safety Hooks

Product information



High quality 2-leg chain sling equipped with self-locking hooks. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.


... [Read more](#)

Marking: According to standard, CE-marked
Standard: EN 818-4

Safety factor: 4:1
Класс: 8

Chain Sling G80 2-leg with Safety Hooks

Blueprint



Technical data

Код товара	Chain diameter mm	WLL ton	EWL m	Бес kg
42070598W	6	1,6	0,5	11,25
42070601W	6	1,6	1	12,05
42070600W	6	1,6	1,5	12,85
42070605W	6	1,6	2	13,65
42070603W	6	1,6	2,5	14,45
42070608W	6	1,6	3	15,25
42070606W	6	1,6	3,5	16,05
42070610W	6	1,6	4	16,85
42070612W	6	1,6	5	18,45
42070614W	6	1,6	6	20,05
42070616W	8	2,8	0,5	16,392
42070620W	8	2,8	1	17,742
42070618W	8	2,8	1,5	19,092
42070328W	8	2,8	2	20,442
42070622W	8	2,8	2,5	21,792
42070034W	8	2,8	3	23,142
42070623W	8	2,8	3,5	24,492
42070624W	8	2,8	4	25,842
42070626W	8	2,8	5	28,542
42070628W	8	2,8	6	31,242
42070550W	10	4,25	0,5	15,35
42070552W	10	4,25	1,5	19,65

Chain Sling G80 2-leg with Safety Hooks

Technical data

Код товара	Chain diameter mm	WLL ton	EWL m	Bec kg
42070349W	10	4,25	1	25,15
42070555W	10	4,25	2,5	26,5
42070372W	10	4,25	3	28,65
42070043W	10	4,25	2	29,45
42070556W	10	4,25	3,5	35,9
42070559W	10	4,25	5	37,25
42070558W	10	4,25	4	38,05
42070561W	10	4,25	6	46,65
42070563W	13	7,5	0,5	23,35
42070566W	13	7,5	1	26,85
42070426W	13	7,5	1,5	30,35
42070425W	13	7,5	2	33,85
42070568W	13	7,5	2,5	37,35
42070572W	13	7,5	3	40,85
42070570W	13	7,5	3,5	44,35
42070574W	13	7,5	4	47,85
42070576W	13	7,5	5	57,4
42070578W	13	7,5	6	64,4
42070584W	16	11,2	1	37,35
42070582W	16	11,2	1,5	42,85
42070588W	16	11,2	2	48,35
42070586W	16	11,2	2,5	53,85
42070396W	16	11,2	3	59,35
42070590W	16	11,2	3,5	64,85
42070592W	16	11,2	4	70,35
42070594W	16	11,2	5	81,35
42070596W	16	11,2	6	92,35