

Chain Sling G80 1-leg with Safety Hook and Grab Hook

Product information



High quality 1-leg chain sling equipped with self-locking hook with shortening hook. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.


... [Read more](#)

Marking: According to standard, CE-marked
Standard: EN 818-4

Safety factor: 4:1
Класс: 8

Chain Sling G80 1-leg with Safety Hook and Grab Hook

Blueprint



Technical data

Код товара	Chain diameter mm	WLL ton	EWL m	Бес kg
42070516W	6	1,12	0,5	8,71
42070519W	6	1,12	1	10,81
42070523W	6	1,12	3,5	11,11
42070518W	6	1,12	1,5	11,21
42070444W	6	1,12	2	11,61
42070525W	6	1,12	3	12,41
42070531W	6	1,12	6	13,11
42070529W	6	1,12	5	14,01
42070521W	6	1,12	2,5	15,41
42070527W	6	1,12	4	16,61
42070533W	8	2	0,5	11,346
42070536W	8	2	1	12,021
42070535W	8	2	1,5	12,696
42070540W	8	2	2	13,371
42070538W	8	2	2,5	14,046
42070105W	8	2	3	14,721
42070542W	8	2	3,5	15,396
42070545W	8	2	4	16,071
42070547W	8	2	5	17,421
42070549W	8	2	6	18,771
42070461W	10	3,15	0,5	20,075
42070463W	10	3,15	1	21,15

Chain Sling G80 1-leg with Safety Hook and Grab Hook

Technical data

Код товара	Chain diameter mm	WLL ton	EWL m	Bec kg
42070462W	10	3,15	1,5	22,225
42070467W	10	3,15	2	23,3
42070465W	10	3,15	2,5	24,375
42070471W	10	3,15	3	25,45
42070469W	10	3,15	3,5	26,525
42070473W	10	3,15	4	27,6
42070475W	10	3,15	5	29,75
42070477W	10	3,15	6	31,9
42070479W	13	5,3	0,5	18,74
42070483W	13	5,3	1	20,49
42070481W	13	5,3	1,5	22,24
42070486W	13	5,3	2	23,99
42070485W	13	5,3	2,5	25,74
42070490W	13	5,3	3	27,49
42070488W	13	5,3	3,5	29,24
42070492W	13	5,3	4	30,99
42070494W	13	5,3	5	34,49
42070496W	13	5,3	6	37,99
42070502W	16	8	1	32,5
42070500W	16	8	1,5	35,25
42070505W	16	8	2	38
42070504W	16	8	2,5	40,75
42070509W	16	8	3	43,5
42070507W	16	8	3,5	46,25
42070401W	16	8	4	49
42070512W	16	8	5	54,5
42070514W	16	8	6	60