



Permanent Lifting Magnet POWERTEX PLM

Product information

POWERTEX



POWERTEX Permanent lifting magnets PLM are very strong, durable and easy to use. The lifting magnets are designed to be versatile and can be used to attach to both flat and circular objects. They need limited maintenance and are designed to keep the lifting capacity over a long lifetime. The PLM magnets are very powerful compared to their dimensions and are light in weight.

Features:

- Safe each lifting magnet is proof load tested to 3,5 x WLL and inspected before leaving the factory
- High quality powerful Neodynium permanent magnets inside
- Light weight
- Designed to lift on both flat and circular surfaces
- Very high safety factor 3,5 (EN 13155 require SF 3)
- The increased safety factor increase life time and assures that standard safety factor 3 can be met also after annual check
- Strong and durable powder painted steel housing with machined connection surface
- Wear and corrosion resistant Chrome plated shackle as top connection
- Handle is equipped with a positive locking device and double locking for extra safety
- RFID equipped (chip) for easy registration, service and inspection
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each lifting magnet
- Spare parts available

Marking: According to standard, CE-marked Standard: EN 13155, AS 4991

Safety factor: 3,5:1.

Код товара	Код	WLL ton	Max. handle turning force kgf	Max. handle turning force kN	A mm	B mm	C mm	D mm	E mm	K mm	L mm	M mm	N mm	O mm	Bec kg
503100010000040	PLM-1	0,1	< 4	0,039	29	71	64	47	29	92	54	130	45	31	3
503100030000040	PLM-3	0,3	< 8	0,078	39	96	88	63	41	165	78	158	63	45	10
503100060000040	PLM-6	0,6	< 8	0,078	51	118	118	74	57	216	114	199	94	57	20
50310010000040	PLM-10	1	< 16	0,157	64	140	148	90	66	286	126	246	106	73	40
50310020000040	PLM-20	2	< 16	0,157	92	188	188	122	82	397	150	375	120	100	95

Blueprint

