CERTEX | Lifting Solutions Group
Axel Johnson International

Push Trolley POWERTEX PPT-S1

Product information



POWERTEX push trolley operated by pushing. A compact and low buildt design with low dead weight in a solid steel construction. It includes mechanical stops to ensure that the trolley is kept on the beam in case of an accident (anti-drop + anti-tilt). Fits most types of beam profiles and most brands of lifting blocks and electric hoists. Wheels with ball bearings.
Supplied with grey label for adhering over white nameplate for use in the entertainment industry.
Static test coefficient: WLL x 1,5.

... *Read more*

Marking: According to standard
Standard: EN 13157

Safety factor: 4:1


Certex Polska
info@certex.pl
+48 91 817 28 49

© October 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Push Trolley POWERTEX PPT-S1

Blueprint



Technical data

Код товара	WLL ton	Beam width mm	Wheel Ø outside/inside mm	Minimum radius mm	Вес kg
502500051800050	0,5	50-180	79/55	800	6
502500101880050	1	66-188	96,2/68	1 000	15
502500202000050	2	88-200	108,2/80	1 100	18
502500302050050	3	100-205	131,3/100	1 300	30
502500502120050	5	114-212	143,7/110	1 400	44
502501002030050	10	124-203	177,45/136	2 000	86

Certex Polska
info@certex.pl
+48 91 817 28 49

© October 2026 - All Rights Reserved