

Crosby Screw Clamp IPSC10 – Not for Lifting

Product information



General:

The IPSC10 screw style clamp is suitable for use in positioning, pulling and turning steel plates and sections.

Features:

- Available in capacities of 1.5 and 3 metric tons.
- Jaw openings available: 0 to 60mm
- Suitable for steel with a surface hardness up to 300 HV10.
- Forged alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.

Marking: CE-marked

| Код товара | WLL ton | Jaw width mm | I P Model. | B mm | C mm | D mm | E mm | F mm | G mm | H mm | J mm | K mm | Bec kg |
|--------------|------------|-----------------|------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|-----------|
| 16.012703857 | 1,5 | 0-40 | 1.5-IPSC | 91 | 143 | 251 | 44 | 156 | 50 | 45 | 16 | 65 | 4,6 |
| 16.012703858 | 3 | 0-60 | 3-IPSC | 109 | 175 | 310 | 51 | 200 | 62 | 55 | 19 | 83 | 8,4 |